

SMALLEY® SPIRAL RETAINING RINGS

Acciaio al Carbonio per Molle
SAE 1070-90

surface treatment:
Oliatura

Esempio di designazione: XAH-37



d1=diametro foro
d2=diametro gola
d3=diametro esterno
S=spessore

Medium duty
series
XAH - per fori
(in pollici)



description	Price Euro x100	% Price Change	Package
XAH-206	160,00	+ 20%	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XAH-206	d2 inch. 2.166 mm 55.02	ring shear Newtons 77.798 L.B.S. 17,491
d1 mm 52.37	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.062	c inch. 0.086 mm 2.18	groove yield Newtons 33.712 L.B.S. 7,579
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.197 mm 55.80		
Toll. d3 inch. +0,046 mm +1,17		
b inch. 0.156 mm 3.96		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.078 mm 1.98		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 10.13		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350