


# SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:  
Oil dipped

Example of designation: HH-37



d1=shaft diameter  
d2=groove diameter  
d3=internal ring diameter  
S=thickness

HH - for bores  
(in inches)



| description | Price<br>Euro x100 | % Price Change | Package |
|-------------|--------------------|----------------|---------|
| HH-225      | 200,00             | + 20%          | 50      |

| DESCRIPTION                          | GROOVE                                 | THRUST CAPACITY                                                                      |
|--------------------------------------|----------------------------------------|--------------------------------------------------------------------------------------|
| HH-225                               | d2 inch. 2.288<br>mm 58.12             | groove yield Newtons 13.442<br>L.B.S. 3,022                                          |
| d1 mm 57.15                          | Toll. d2 inch. +/-0,006<br>mm +/- 0,15 | (based on a groove material yield<br>strength of 310/mm and a safety factor<br>of 2) |
| d1 inch 2.250                        | c inch. 0.193<br>mm 4.90               |                                                                                      |
|                                      | Toll. c inch. +0,004<br>mm +0,100      |                                                                                      |
| RING IN THE UNSTRESSED STATE         |                                        |                                                                                      |
| d3 inch. 2.333<br>mm 59.26           |                                        |                                                                                      |
| Toll. d3 inch. +0,024<br>mm +0,61    |                                        |                                                                                      |
| b inch. 0.038<br>mm 0.97             |                                        |                                                                                      |
| Toll. b inch. +/-0,002<br>mm +/-0,05 |                                        |                                                                                      |
| s inch. 0.187<br>mm 4.75             |                                        |                                                                                      |
| Toll. s inch. +/-0,005<br>mm +/-0,13 |                                        |                                                                                      |
| Weight Kg/1000 6.61                  |                                        |                                                                                      |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350