

**TECHNICAL PLASTIC AND METAL PARTS** 

						0	ver cap <b>06-k4</b>
Code	Description	Price euro/1000	% Price Change 1 2	Package	A	В	CDEFgr
006 5042 197 04	MP 06- 5- 4 CAPP.197	83,00	+ 60% -	250	10.8	12.2	6

Colour	Colour numbe	er				
yellow	197 (XXX XXXX <b>XXX</b> XX)					
Colour descriptionyellowMatchessand yelloFeatured colours reserved. Due to the		y matches RAL colour 1002 and PL in colour may occur.	_ 731			
Material Material nr						
polyethylene Hd - PE		04 (XXX XXXX XXX <b>XX</b> )				
General informations: High pressure Polyethylene is resistant a little less than low pressure Polyethy insulating electrically. Polyethylene car Features	ylene, yet has a bette	er scratch firmness. Does not take				
feature	DIN	Resistance to	Valutation			
Relative density gr/cm <sup>3</sup>	0.95	Petrol	A			
Tensile strength MN/m <sup>2</sup>	24	Benzene	A			
Elongation at break %	350	Mineral oils	A			
Tensile modulus MN/m <sup>2</sup>	1000	Vegetable oils	A			
Notched impact strength kJ/m <sup>2</sup>	3	Weak alkalis	A			
Ball indentation MN/m <sup>2</sup>	25	Strong alkalis	А			
Application temperature max °C	80	Weak acids	А			
Volume resistivity cm	10^15	Strong acids	В			
Dissapation factor tan. 10 <sup>3</sup> Hz	0,001	A = good				
Dielectric strength MV/m	53	<b>B</b> = doubtful				
Flammability UL94 > 1,6 mm	-	<b>C</b> = poor				
Coefficient of friction (on steel)	0,25-0,3					

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

**GANDINI FASTENERS SRL** Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350