

TECHNICAL PLASTIC AND METAL PARTS

							ver cap 06-k4
Code	Description	Price euro/1000	% Price Change 1 2	Package	А	В	CDEFgr
006 5042 195 04	MP 06- 5- 4 CAPP.195	83,00	+ 60% -	250	10.8	12.2	6

Colour	Colour numbe							
beige	9 195 (XXX XXX XXX XX)							
Colour descriptionbeigeMatchesbeigeFeatured colours reserved. Due to the	e. Matches: Reasona	ably matches RAL colour 1001 in colour may occur.						
Material	Material nr							
polyethylene Hd - PE		04 (XXX XXXX XXX XX)						
High pressure Polyethylene is resistar a little less than low pressure Polyethy insulating electrically. Polyethylene ca	lene, yet has a bette	er scratch firmness. Does not take burns on after lighting it.						
Features		Chimical resistance						
feature	DIN	Resistance to	Valutation					
Relative density gr/cm ³	0,95	Petrol	А					
Tensile strength MN/m ²	24	Benzene	А					
Elongation at break %	350	Mineral oils	А					
Tensile modulus MN/m ²	1000	Vegetable oils	А					
Notched impact strength kJ/m ²	3	Weak alkalis	A					
Ball indentation MN/m ²	25	Strong alkalis	A					
Application temperature max °C	80	Weak acids	A					
Volume resistivity cm	10^15	Strong acids	В					
Dissapation factor tan. 10 ³ Hz	0,001	A = good						
Dielectric strength MV/m	53	B = doubtful						
Flammability UL94 > 1,6 mm	-	C = poor						
Coefficient of friction (on steel)	0,25-0,3							
All data are indicative								

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350