

Metallic screws and nuts


1) A light rounding-off or a countersink between the head and the hexagon socket is allowed.

2) The superior side of the head can be rounded or blunt as per manufacturer directives.

$lg_{max} = l - b$

$ls_{min} = lg_{max} - 5p$

On request: AISI 304 - 316 - 410 materials



Hexagonal socket countersunk head screws
UNI 5933 DIN 7991-A
Class 10.9 Zinc plated



Description	Price VAT excl. euro/100	% Price Change 1	% Price Change 2	Package	d mm	L mm
M 5 X 18 ZINCATE	5,40	+ 60%	-	1	M5	18

M 5 X 18 ZINCATE	da	max	5.7	s	nom	3
p	0.8	e	min	3.44	max	3.1
lg	max	5.2	k	max	2.8	3.02
dk	max	10	r	min	0.2	2.3
	min	9.64				2.05

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S. Giovanni Milano Italy

Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350