

Metallic screws and nuts

****Per diametri M10**, M12**, M14**, M22** la ISO 8765 prevede valori s, e, dw differenziati da UNI e DIN**

Tolleranze: categoria A e B secondo disponibilità di magazzino

A richiesta: diametri >M30 - lunghezze >300

$lg_{max} = l - b$

$ls_{min} = lg_{max} - 5p$

A richiesta: in materiale AISI 304 - 316 - 410 - B7 - L7



Hexagonal head screws
ISO 8765 - UNI 5738
DIN 960
gambo parzialm. filettato
Classe 10.9 Zincate



Description	Price VATexcl. euro/100	% Price Change 1 2	Package	d mm	L mm
M 22 X 140 ZINCATE	on demand	- -	1	M22	140

M 22 X 140 ZINCATE			da	max	24,4	k	nom	14
p		1,5	ds	max	22		min cat. A	13,785
b	I ≤ 125	50		min cat. A	21,67		max cat. A	14,215
	125 < I ≤ 200	56	dw	min	30	kw	min cat. A	9,65
	I > 200	69	e	min cat. A	35,72	r	min	0,8
c	max	0,8	lf	max	4	s	max	32
	min	0,2					min cat. A	31,61

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL Sales department
viale Pier Paolo Pasolini, 83 250@gandini.it
Sesto San Giovanni Mi - Italy tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350