

Metallic screws and nuts

****Per diametri M10**, M12**, M14**, M22** la ISO 8765 prevede valori s, e, dw differenziati da UNI e DIN**


Tolleranze: categoria A e B secondo disponibilità di magazzino

A richiesta: diametri >M30 - lunghezze >300

$lg_{max} = l - b$

$ls_{min} = lg_{max} - 5p$

A richiesta: in materiale AISI 304 - 316 - 410 - B7 - L7



Hexagonal head screws
ISO 8765 - UNI 5738
DIN 960
gambo parzialm. filettato
Classe 10.9 Zincate



Description	Price VATexcl. euro/100	% Price Change 1	% Price Change 2	Package	d mm	L mm
M 20 X 55 ZINCATE	on demand	-	-	1	M20	55

M 20 X 55 ZINCATE			da	max	22,4	k	nom	12,5
p		1,5	ds	max	20		min cat. A	12,285
b	I ≤ 125	46		min cat. A	19,67		max cat. A	12,715
	125 < I ≤ 200	52	dw	min	28,19	kw	min cat. A	8,6
	I > 200	65	e	min cat. A	33,53	r	min	0,8
c	max	0,8	lf	max	4	s	max	30
	min	0,2					min cat. A	29,67

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL Sales department
viale Pier Paolo Pasolini, 83 250@gandini.it
Sesto San Giovanni Mi - Italy tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350