


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XAH-37

Medium duty
series
**XAH - for bores
(in inches)**


description	Price Euro x100	% Price Change	Package
XAH-362	550,00	+ 20%	50

DESCRIPTION	GROOVE	THRUST CAPACITY
XAH-362	d2 inch. 3.773 mm 95.83	ring shear Newtons 184.351 L.B.S. 41,446
d1 mm 92.08	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 3.625	c inch. 0.120 mm 3.05	groove yield Newtons 84.341 L.B.S. 18,961
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 3.831 mm 97.31		
Toll. d3 inch. +0,078 mm +1,98		
b inch. 0.250 mm 6.35		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.109 mm 2.77		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 39.80		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350