


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: XDS-50



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
s=thickness

Light duty series
XDS - for shafts
(in inches)



description	Price Euro x100	% Price Change	Package
XDS-312	180,00	+ 20%	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XDS-312	d2 inch. 3.000 mm 76.20	ring shear Newtons 97.904 L.B.S. 22,011 (safety factor =3)
d1 mm 79.38	Toll. d2 inch. +/-0,006 mm +/-0,15	groove yield Newtons 61.408 L.B.S. 13,806 (based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 inch 3.125	c inch. 0.068 mm 1.73	
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	
d3 inch. 2.965 mm 75.31		
Toll. d3 inch. -0,078 mm -1,98		
b inch. 0.187 mm 4.75		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 14.56		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350