


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: XDS-50



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
s=thickness

Light duty series
XDS - for shafts
(in inches)



description	Price Euro x100	% Price Change		Package
XDS-275	150,00	1 + 20%	2 -	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XDS-275	d2 inch. 2.626 mm 66.70	ring shear Newtons 86.155 L.B.S. 19,369
d1 mm 69.85	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.750	c inch. 0.068 mm 1.73	groove yield Newtons 53.607 L.B.S. 12,052
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.596 mm 65.94	Toll. c inch. +0,004 mm +0,100	
Toll. d3 inch. -0,078 mm -1,98		
b inch. 0.187 mm 4.75		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 12.84		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350