

**SMALLEY® SPIRAL RETAINING RINGS**
**SAE 1070-90 Carbon Steel**

surface treatment:  
**Oil dipped**
**Example of designation: XDS-50**

**d1**=shaft diameter  
**d2**=groove diameter  
**d3**=internal ring diameter  
**S**=thickness

Light duty series  
**XDS - for shafts**  
(in inches)


| description   | Price<br>Euro x100 | % Price Change |        | Package |
|---------------|--------------------|----------------|--------|---------|
| <b>XDS-87</b> | <b>44,00</b>       | 1<br>+ 20%     | 2<br>- | 500     |

| DESCRIPTION                                 | GROOVE                                       | THRUST CAPACITY                                                                |
|---------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------|
| XDS-87                                      | <b>d2</b> inch. 0.833<br>mm 21.16            | <b>ring shear</b> Newtons 19.563<br>L.B.S. 4,398                               |
| <b>d1 mm</b> 22.23                          | <b>Toll. d2</b> inch. +/-0,003<br>mm +/-0,08 | (safety factor =3)                                                             |
| <b>d1 inch</b> 0.875                        | <b>c</b> inch. 0.046<br>mm 1.17              | <b>groove yield</b> Newtons 5.777<br>L.B.S. 1,299                              |
| <b>RING IN THE UNSTRESSED STATE</b>         | <b>Toll. c</b> inch. +0,003<br>mm +0,080     | (based on a groove material yield strength of 310/mm and a safety factor of 2) |
| <b>d3</b> inch. 0.823<br>mm 20.90           |                                              |                                                                                |
| <b>Toll. d3</b> inch. -0,031<br>mm -0,79    |                                              |                                                                                |
| <b>b</b> inch. 0.093<br>mm 2.36             |                                              |                                                                                |
| <b>Toll. b</b> inch. +/-0,003<br>mm +/-0,08 |                                              |                                                                                |
| <b>s</b> inch. 0.042<br>mm 1.07             |                                              |                                                                                |
| <b>Toll. s</b> inch. +/-0,002<br>mm +/-0,05 |                                              |                                                                                |
| <b>Weight Kg/1000</b> 1.42                  |                                              |                                                                                |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350