


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XDS-50

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Light duty series
XDS - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XDS-475	590,00	+ 20%	-	25

DESCRIPTION	GROOVE	THRUST CAPACITY
XDS-475	d2 inch. 4.610 mm 117.09	ring shear Newtons 179.214 L.B.S. 40,291
d1 mm 120.65	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 4.750	c inch. 0.086 mm 2.18	groove yield Newtons 104.542 L.B.S. 23,503
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 4.560 mm 115.82	Toll. c inch. +0,005 mm +0,130	
Toll. d3 inch. -0,093 mm -2,36		
b inch. 0.218 mm 5.54		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.078 mm 1.98		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 32.46		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350