


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XDH-112

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Light duty series
XDH - for bores
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XDH-725	1.000,00	+ 20%	-	25

DESCRIPTION	GROOVE	THRUST CAPACITY
XDH-725	d2 inch. 7.410 mm 188.21	ring shear Newtons 328.245 L.B.S. 73,796
d1 mm 184.15	Toll. d2 inch. +/-0,008 mm +/-0,2	(safety factor =3)
d1 inch 7.250	c inch. 0.103 mm 2.62	groove yield Newtons 182.358 L.B.S. 40,998
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 7.500 mm 190.50		
Toll. d3 inch. +0,187 mm +4,75		
b inch. 0.250 mm 6.35		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 68.89		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350