


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WSM-25

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty
series
WSM - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
WSM-350	330,00	+ 20%	-	50

DESCRIPTION	GROOVE	THRUST CAPACITY
WSM-350	d2 inch. 3.316 mm 84.23	ring shear Newtons 217.151 L.B.S. 48,820
d1 mm 88.90	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 3.500	c inch. 0.120 mm 3.05	groove yield Newtons 101.236 L.B.S. 22,760
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 3.293 mm 83.64		
Toll. d3 inch. -0,035 mm -0,89		
b inch. 0.270 mm 6.86		
Toll. b inch. +0,004/-0,006 mm +0,10/-0,15		
s inch. 0.111 mm 2.82		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 40.96		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350