

SMALLEY® SPIRAL RETAINING RINGS

SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WH-50



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium duty series
WH - for bores
(in inches)



description	Price Euro x100	% Price Change		Package
		1	2	
WH-90	21,00	+ 20%	-	500

DESCRIPTION	GROOVE	THRUST CAPACITY
WH-90	d2 inch. 0.939 mm 23.85	ring shear Newtons 18.059 L.B.S. 4,060
d1 mm 23.01	Toll. d2 inch. +/-0,003 mm +/-0,08	(safety factor =3)
d1 inch 0.906	c inch. 0.036 mm 0.91	groove yield Newtons 5.427 L.B.S. 1,220
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 0.949 mm 24.10	Toll. c inch. +0,003 mm +0,080	
Toll. d3 inch. +0,013 mm +0,33		
b inch. 0.065 mm 1.65		
Toll. b inch. +0,003/-0,005 mm +0,08/-0,13		
s inch. 0.031 mm 0.79		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 0.69		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350