


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: VS-25

**Light duty series
VS - for shafts
(in inches)**

**d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness**

description	Price Euro x100	% Price Change		Package
		1	2	
VS-318	66,00	+ 20%	-	100

DESCRIPTION		GROOVE		THRUST CAPACITY	
VS-318		d2		ring shear	
d1 mm	80.95	inch. 3.095 mm 78.61		Newtons 72.947 L.B.S. 16,400	
d1 inch	3.187	Toll. d2		(safety factor =3)	
		inch. +/-0,006 mm +/-0,15		groove yield	
		c		Newtons 46.081 L.B.S. 10,360	
		inch. 0.044 mm 1.12		(based on a groove material yield strength of 310/mm and a safety factor of 2)	
		Toll. c			
		inch. +0,003 mm +0,080			
RING IN THE UNSTRESSED STATE					
d3	inch. 3.062 mm 77.77				
Toll. d3	inch. -0,03 mm -0,76				
b	inch. 0.188 mm 4.78				
Toll. b	inch. +/-0,005 mm +/-0,13				
s	inch. 0.039 mm 0.99				
Toll. s	inch. +/-0,002 mm +/-0,05				
Weight Kg/1000	9.12				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350