


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: VS-25

**Light duty series
VS - for shafts
(in inches)**

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

description	Price Euro x100	% Price Change		Package
		1	2	
VS-62	14,80	+ 20%	-	1000

DESCRIPTION	
VS-62	
d1 mm	15.88
d1 inch	0.625

RING IN THE UNSTRESSED STATE	
d3	inch. 0.591 mm 15.01
Toll. d3	inch. -0,013 mm -0,33
b	inch. 0.045 mm 1.14
Toll. b	inch. +/-0,004 mm +/-0,10
s	inch. 0.018 mm 0.46
Toll. s	inch. +/-0,0015 mm +/-0,04
Weight Kg/1000	0.18

GROOVE	
d2	inch. 0.597 mm 15.16
Toll. d2	inch. +/-0,002 mm +/-0,05
c	inch. 0.022 mm 0.56
Toll. c	inch. +0,002 mm +0,050

THRUST CAPACITY	
ring shear	Newtons 7.250 L.B.S. 1,630 (safety factor =3)
groove yield	Newtons 2.758 L.B.S. 620 (based on a groove material yield strength of 310/mm and a safety factor of 2)

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350