

**SMALLEY® SPIRAL RETAINING RINGS**
**SAE 1070-90 Carbon Steel**

surface treatment:  
**Oil dipped**
**Example of designation: HSM-10**

**d1**=shaft diameter  
**d2**=groove diameter  
**d3**=internal ring diameter  
**S**=thickness

**HSM - for shafts**


| description   | Price<br>Euro x100 | % Price Change |        | Package |
|---------------|--------------------|----------------|--------|---------|
| <b>HSM-56</b> | <b>220,00</b>      | 1<br>+ 20%     | 2<br>- | 50      |

| DESCRIPTION                         | GROOVE          | THRUST CAPACITY                                                                                                      |
|-------------------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------|
| HSM-56                              | <b>d2</b>       | <b>groove yield</b> Newtons 13.160<br>(based on a groove material yield strength of 310/mm and a safety factor of 2) |
| <b>d1 mm</b> 56.00                  | mm 55.03        |                                                                                                                      |
|                                     | <b>Toll. d2</b> |                                                                                                                      |
|                                     | mm +/-0,15      |                                                                                                                      |
|                                     | <b>c</b>        |                                                                                                                      |
|                                     | mm 4.90         |                                                                                                                      |
|                                     | <b>Toll. c</b>  |                                                                                                                      |
|                                     | mm +0,100       |                                                                                                                      |
| <b>RING IN THE UNSTRESSED STATE</b> |                 |                                                                                                                      |
| <b>d3</b>                           | mm 53.91        |                                                                                                                      |
| <b>Toll. d3</b>                     | mm -0,61        |                                                                                                                      |
| <b>b</b>                            | mm 0.97         |                                                                                                                      |
| <b>Toll. b</b>                      | mm +/-0,05      |                                                                                                                      |
| <b>s</b>                            | mm 4.75         |                                                                                                                      |
| <b>Toll. s</b>                      | mm +/-0,13      |                                                                                                                      |
| <b>Weight Kg/1000</b>               | 6.19            |                                                                                                                      |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
 Tel. +39 02 241 047 250 Fax +39 02 241 047 74

 Production and distribution  
 of fasteners, fixing elements  
 and mechanical parts  
 machining

**GANDINI FASTENERS SRL**  
 viale Pier Paolo Pasolini, 83  
 Sesto San Giovanni Mi - Italy

**Sales department**  
 250@gandini.it  
 tel +39 02 241 047 250

**Administration**  
 350@gandini.it  
 tel +39 02 241 047 350