


SMALLEY® SPIRAL RETAINING RINGS

Stainless steel
AISI 302

surface treatment:
Steam degreasing
Ultrasonic cleaning

Example of designation: FH-013-S02



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Heavy duty
series
FH - for bores
for groove DIN
472



description	Price Euro x100	% Price Change		Package
FH-070-S02	650,00	1 + 20%	2 -	100

DESCRIPTION	GROOVE	THRUST CAPACITY
FH-070-S02	d2	ring shear Newtons 125.489 (safety factor =3)
d1 mm 70.00	Toll. d2 mm +0,3	groove yield Newtons 51.128 (based on a groove material yield strength of 310/mm and a safety factor of 2)
RING IN THE UNSTRESSED STATE	c	
d3 mm 73.64	Toll. c mm +0,140	
Toll. d3 mm +00,76		
b mm 5.08		
Toll. b mm +/-0.13		
s mm 2.41		
Toll. s mm +/-0,08		
Weight Kg/1000 18.12		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350