


SMALLEY® SPIRAL RETAINING RINGS

Acciaio al Carbonio per Molle
SAE 1070-90

surface treatment:
Oliatura

Esempio di designazione: VHM-6



Light duty series
VHM - per fori



d1=diametro foro
d2=diametro gola
d3=diametro esterno anello
S=spessore

description	Price Euro x100	% Price Change		Package
		1	2	
VHM-88	79,00	+ 20%	-	50

DESCRIPTION	GROOVE	THRUST CAPACITY
VHM-88	d2	ring shear Newtons 79.257 (safety factor =3)
d1 mm 88,00	mm 90,34	
	Toll. d2	groove yield Newtons 50,179 (based on a groove material yield strength of 310/mm and a safety factor of 2)
	mm +/-0,15	
RING IN THE UNSTRESSED STATE	c	
d3	mm 1,12	
mm 91,32	Toll. c	
Toll. d3	mm +0,080	
mm +0,76		
b		
mm 4,78		
Toll. b		
mm +/-0,13		
s		
mm 0,99		
Toll. s		
mm +/-0,05		
Weight Kg/1000		
10,09		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350