

TECHNICAL PLASTIC AND METAL PARTS

Ventilation cover
123

Code	Description	Price euro/1000	% Price Change	Package	A	B	C	D	E	F	gr
123 1043 002 01	MP 123-1043 GRIGIO	572,00	1 + 60%	50	50	43	12			F1	

Colour	Colour number
grey	002 (XXX XXXX XXX XX)
Colour description	grey
Matches	Grey. Matches: Reasonably matches RAL colour 7000.
Featured colours reserved. Due to the screen, differences in colour may occur.	

Material	Material nr
Nylon - 6 PA - 6	01 (XXX XXXX XXX XX)
General informations: A strong, tough and durable material. Suitable for connecting elements and other technical components. Owing to self lubricant properties ideal for slide bearings. Takes in approx 3% moisture at room temperature and is then at its strongest. Always has to acclimatize for a few days. Operational temperature up to approx 120°C. Nylon is self extinguishing.	
Features	
feature	DIN
Relative density gr/cm ³	1,14
Tensile strength MN/m ²	55
Elongation at break %	250
Tensile modulus MN/m ²	950
Notched impact strength kJ/m ²	35
Ball indentation MN/m ²	82
Application temperature max °C	120
Volume resistivity cm	10^15
Dissapation factor tan. 10 ³ Hz	0,2
Dielectric strength MV/m	35
Flammability UL94 > 1,6 mm	V2
Coefficient of friction (on steel)	0,3
All data are indicative	
Chimical resistance	
Resistance to	Valutation
Petrol	A
Benzene	A
Mineral oils	A
Vegetable oils	A
Weak alkalis	A
Strong alkalis	B
Weak acids	B
Strong acids	C
A = good B = doubtful C = poor	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350