

TECHNICAL PLASTIC AND METAL PARTS

Photo clip
046

Code	Description	Price euro/1000	% Price Change	Package	A	B	C	D	E	F	gr
			1 2								
046 0250 000 26	MP 46-2,5	159,00	+ 60%	-	250	2.4	2.5	10	1.5	15	F1

Colour	Colour number
transparent - natural	000 (XXX XXXX XXX XX)
Colour description	transparent - natural
Matches	Natural matches Milk-like; transparent white colour can differ per kind of material.
Featured colours reserved. Due to the screen, differences in colour may occur.	

Material		Material nr	
Sealon -		26 (XXX XXXX XXX XX)	
General informations:			
A strong plastic which is extremely suitable for application to cold formable plastic products, such as rivets or synthetic lead seals.			
Features		Chemical resistance	
feature	DIN	Resistance to	Valutation
Relative density gr/cm ³	1,01	Petrol	B
Tensile strength MN/m ²	26	Benzene	C
Elongation at break %	150	Mineral oils	B
Tensile modulus MN/m ²	1400	Vegetable oils	A
Notched impact strength kJ/m ²	4	Weak alkalis	A
Ball indentation MN/m ²	-	Strong alkalis	A
Application temperature max °C	85	Weak acids	A
Volume resistivity cm	10^15	Strong acids	A
Dissapation factor tan. 10 ³ Hz	-	A = good	
Dielectric strength MV/m	-	B = doubtful	
Flammability UL94 > 1,6 mm	HB	C = poor	
Coefficient of friction (on steel)	-		
All data are indicative			

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350