

## Metallic screws and nuts

ISO 4014 foresees s, e, dw values different by UNI and DIN for M10, M12, M14, M22 diameters

Tolerance: A and B category according to stock availability

On request: diameters >M30 - length >300

$lg_{max} = l - b$

$ls_{min} = lg_{max} - 5p$

On request: AISI 304 - 316 - 410 - B7 - L7 materials



Hexagonal head screws  
ISO 4014 - UNI 5737  
DIN 931  
partially threaded  
Class 8.8 Zinc plated



| Description        | Price VATexcl.<br>euro/100 | % Price Change | Package | d mm | L mm |
|--------------------|----------------------------|----------------|---------|------|------|
| M 10 X 210 ZINCATE | 216,00                     | + 60%          | 1       | M10  | 210  |

|                    |            |                                     |     |            |            |       |            |      |            |      |     |     |
|--------------------|------------|-------------------------------------|-----|------------|------------|-------|------------|------|------------|------|-----|-----|
| M 10 X 210 ZINCATE |            |                                     | da  | max        | 11.2       | k     | nom        | 6.4  |            |      |     |     |
| p                  | 1.5        | l ≤ 125<br>125 < l ≤ 200<br>l > 200 | ds  | max        | 10         |       | min cat. A | 6.22 |            |      |     |     |
|                    |            |                                     |     | min cat. A | 9.78       |       | max cat. A | 6.58 |            |      |     |     |
|                    |            |                                     |     | b          | dw         | min   | 15.6       | kw   | min cat. A | 4.35 |     |     |
| e                  | min cat. A | 18.9                                | r   |            |            |       |            |      |            |      | min | 0.4 |
|                    |            |                                     |     |            |            |       |            |      |            |      |     |     |
| c                  | max        | 0.6                                 | min | 0.15       | min cat. A | 16.73 |            |      |            |      |     |     |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL** Sales department  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350