

Metallic screws and nuts

ISO 8765 foresees s, e, dw values different by UNI and DIN for M10, M12, M14, M22 diameters

Tolerance: A and B category according to stock availability

On request: diameters >M30 - length >300

$lg_{max} = l - b$

$ls_{min} = lg_{max} - 5p$

On request: AISI 304 - 316 - 410 - B7 - L7 materials



Hexagonal head screws
ISO 8765 - UNI 5738
DIN 960
partially threaded
Class 8.8 Zinc plated



Description	Price VATexcl. euro/100	% Price Change	Package	d mm	L mm
M 16 X 260 ZINCATE	on demand	-	1	M16	260

M 16 X 260 ZINCATE		da	max	17.7	k	nom	10
p	1.5	ds	max	16		min cat. A	9.82
			min cat. A	15.73		max cat. A	10.18
b	$l \leq 125$	dw	min	22.49	kw	min cat. A	6.87
	$125 < l \leq 200$		e	min cat. A		min	0.6
	$l > 200$		If	max	s	max	24
c	max	If	max	3	s	min cat. A	23.67
	min		min	0.2			

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL Sales department
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350