

Metallic screws and nuts

ISO 4014 foresees s, e, dw values different by UNI and DIN for M10, M12, M14, M22 diameters


Tolerance: A and B category according to stock availability

On request: diameters >M30 - length >300

$$lg \max = l - b$$

$$l_s \text{ min} = l_g \text{ max} - 5p$$

On request: AISI 304 - 316 - 410 - B7 - L7 materials



Hexagonal head screws
ISO 4014 - UNI 5737
DIN 931
partially threaded
Class 8.8 Zinc plated



Description	Price VATexcl. euro/100	% Price Change 1 2	Package	d mm	L mm
M 30 X 95 ZINCATE	on demand	- -	1	M30	95

M 30 X 95 ZINCATE			da	max	33.4	k	nom	18.7
p		3.5	ds	max	30		min cat. A	
b	I ≤ 125	66		min cat. A			max cat. A	
	125 < I ≤ 200	72	dw	min			min cat. A	
	I > 200	85	e	min cat. A		r	min	1
c	max	0.2	lf	max	6	s	max	46
	min	0.8					min cat. A	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL Sales department
viale Pier Paolo Pasolini, 83 250@gandini.it
Sesto San Giovanni Mi - Italy tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350