

Viti e dadi

1) A light rounding-off or a countersink between the head and the hexagon socket is allowed.

2) The superior side of the head can be rounded or blunt as per manufacturer directives.

3) The inferior side of the head can be rounded or blunt to dw, in both cases it will be without rags.

$l_g \max = l - b$


$l_s \min = l_g \max - 5p$

$l_f \max = 1,7 r \max$

$r \max = d_a \max - d_s \max : 2$

On request: diameters >M24

On request: AISI 304 - 316 - 410 - B7 - L7 materials



Viti a testa cilindrica con
cava esagonale
ISO 4762 UNI 5931
DIN 912
Class 8.8 Zinc plated



Descrizione	Prezzo IVA escl. euro/100	% Price Change	Package	d mm	L mm
M 6 X 90 ZINCATE	33,80	+ 60%	1	M6	90

M 6 X 90 ZINCATE			ds	max	6		nom	5
p				min	5.82	s	max	5.14
b			e	min	5.723		min	5.02
			lf	max	0.68	t	min	3
dk			k	max	6	v	max	0.6
				min	5.7	dw	min	9.38
da			r	min	0.25	w	min	2.3

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy

Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Produzione e distribuzione
fasteners, elementi di
fissaggio e lavorazioni
meccaniche

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Uffici Commerciali
250@gandini.it
tel +39 02 241 047 250

Amministrazione
350@gandini.it
tel +39 02 241 047 350